


PS Series

Standard Efficiency Pleated Filter Cartridges



*Residential/Commercial/Industrial
Filtration Applications*

Standard Features

- Manufactured in China
- Special non-cellulose fabric provides excellent resistance to bacterial and chemical attack
- Long service life and reduced maintenance costs
- Synthetic polyester fabric pleated around a durable polypropylene core
- Filters available in standard 2-1/2" and 4-1/2" cartridge diameters

Product Specifications

Micron Sizes

0.35, 1, 1A, 5, 10, 20, 50, and 100 microns

Cartridge Lengths

9-3/4", 20", 30", and 40"

Outside Diameters

2-3/4" and 4-1/2" OD

Operating Temperature

40°F - 180°F (4.4°C - 82.2°C) temperature limit*

Initial Pressure Drop

< 1 psi typical

Materials of Construction


Filter Media: Pleated Polyester

Core: Polypropylene

*Temperature limits vary and depend on pressure and time under load

Applications

- Drinking Water
- Reverse Osmosis Prefiltration
- Water




Ordering Guide (Example: PS-27300-20)

PS	-	27	300	-	20
TYPE	MEDIA	CARTRIDGE DIAMETER	CARTRIDGE LENGTH	MICRON RATING	
PS = Pleated Standard Polypropylene (standard)	Blank = Pleated Polyester	27 = 2 3/4" 45 = 4 1/2"	097 = 9 3/4" 200 = 20" 300 = 30" 400 = 40"	s35 = 0.35 01 = 1 1A = 1 Abs 05 = 5 10 = 10 20 = 20 50 = 50 100 = 100	Brown ** Tan Purple White Red Blue Yellow Green

** End cap color. End caps available only on 2 3/4" cartridges.

Dimensions



Case Packs

DIMENSIONS	QUANTITY
2-3/4" x 9-3/4"	50
2-3/4" x 19-1/2"	25
2-3/4" x 20"	25
2-3/4" x 29-1/4"	25
2-3/4" x 30"	25
2-3/4" x 40"	25
4-1/2" x 9-3/4"	12
4-1/2" x 20"	6



**Filter Housings
Selection Guide**
[CLICK HERE](#)



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008
Tel 855.896.3525 · Fax 866.409.9622
www.neologicsolutions.com · info@neologicsolutions.com
STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA

QUESTIONS?

Ask one of our Service Representatives:
Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

We ship six
days a week!

