

MBG-25 Series

Sediment Grooved Cartridges

neo·PURE™



Residential/Commercial Filtration Applications

Standard Features

- Dependable and cost-effective solution for pre-filtration for the food and beverage industry
- Grooves create increased surface area for longer cartridge life and high dirt-holding capacity
- Melt blown polypropylene filter media
- Provides excellent prefiltration in reverse osmosis systems, UV systems, and beverage filtration systems
- Filters for particulates, sediment, dirt, and rust
- Direct replacement for AP110 / AP124

Product Specifications

Filter Media

Polypropylene

Micron Rating (Nominal)

5, 20, 50 microns

Dimensions

2-1/2" diameter x 9-7/8"

Cartridge Style

Drop-In

Operating Temperature

40° F to 145° F (4.4° C to 62.8° C)

Maximum Pressure Drop

69° F (20° C) 46.4 psi (3.2 kg/cm²)

Recommended Replaceable Pressure Drop

21.75 psi (3.2 kg/cm²)

Maximum Flow

8 gpm

Case Pack

50 per case

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Applications

- Beverages
- Electronics
- Fine Chemicals
- Plating Solutions
- Potable Water
- Prefiltration for Reverse Osmosis



Tested and certified by NSF International against NSF/ANSI Standard 42 for material safety only

United Water Product Guide

Model	Length	Micron
MBG-25098-05	9-7/8"	5
MBG-25098-20	9-7/8"	20
MBG-25098-50	9-7/8"	50



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008

Tel 855.896.3525 · Fax 866.409.9622

www.neologicsolutions.com · info@neologicsolutions.com

STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA

QUESTIONS?

Ask one of our Service Representatives:
Mon-Fri 8a-8p, Sat 8:30a-4:30p EST